


GM82020 PC control

Product Specification for Fast Tunable Laser

Source Module





Overview

The GM82020 fast tunable laser source module is mainly used for the measurement and application of high-precision wavelength division multiplexing DWDM components, optical waveguide grating array AWG components, planar optical waveguide PLC components, optical amplifiers EDFA and other general fiber optics, and is especially suitable for the fast scanning test of fiber grating sensors. The GM82020 series of modules offer superior performance with a wavelength scanning speed of 30 nm/s (10pm step).

The GM82020 fast tunable laser module can be connected to a computer via a USB cable and communicates with the PC control software provided by UC Instruments to form a tunable laser source measurement system with high precision, high power, compact size, fast startup and low price. Our company can provide C-band and L-band GM82020 tunable laser light source modules for users to choose. At the same time, this series of modules can be specially customized and controlled through RS232 interface.

The BNC output trigger port is integrated into the customer's production system.



Characteristic

high power;
fast tuning speed;
PC software control
High wavelength precisio;
continuous wavelength tuning,;
Small form factor for integration into customer product systems

Application

Testing of filters :
scanning spectral analysis
Passive optical devices
Optical path adjustment monitoring
Measurement of fiber grating sensors Laser
optical devices Measurement of WSS, PLC and AWG components and modules



Performance indicators

Product model	GM82020C
Wavelength adjustable range	41 nm
Minimum wavelength value	≤ 1527 nm
Maximum wavelength value	≥ 1568 nm
Output Power	≥ 10 dBm
Wavelength resolution	1.0 pm
Absolute wavelength accuracy	± 10 pm, typ. < 5 pm
Relative wavelength accuracy	± 5 pm, typ ± 2 pm
Wavelength repeatability	± 2 pm, typ. ± 1 pm
Wavelength stability	$\leq \pm 2$ pm
Tuning speed	Typical value: ≤ 0.2 ms
Scanning speed	≤ 30 nm/sec (10 pm step)
Power stability	± 0.05 dB (1 hour). Typical value: ± 0.1 dB (24 hours)
Power repeatability	± 0.05 dB
Power linearity	± 0.3 dB
Power wavelength flatness	0.3 dB typical, 0.5 dB maximum
Side mode suppression ratio	≥ 45 dB
Relative noise intensity	< -135 dB



Optical output interface	PM, FC/PC connector
Communication interface	RS232
Trigger output port	BNC trigger
Power supply power	12 V; 1A
Starting current	$\leq 1A$
Operating current	$\leq 120mA$
Operating current at room temperature	$\leq 100mA$
Cold start time	≤ 10 seconds
Hot start time	≤ 3 seconds
Overall dimensions	40 mm X 150 mm X 170 mm

Technical support and services

We provide our customers with high performance, high quality and low price measuring instruments and test systems. Our powerful technical resources can help you select and use the right products to meet your application needs. Every instrument we sell is backed by a worldwide warranty that provides a minimum of 12 months of factory warranty.

Our commitment

All of our measuring instruments and test systems meet the functional and performance specifications described in our literature. Once you choose our products, we will provide you with qualified products and product operation methods. For use with special functions, we will provide basic measurement assistance.